

Safety Tester/Hipot Tester

IV. TH9130 Series Multifunction Safety Compliance Analyzer

NEW

Features

- 7-inch capacitive touch screen, 800×480 resolution Linux operating system
- Seven-in-one comprehensive test system with the following functions:
 - 1) AC withstand voltage test
 - 2) DC withstand voltage test
 - 3) Insulation resistance test
 - 4) Ground bond test
 - 5) Continuity test
 - 6) Leakage current test
 - 7) Electrical performance test
- 500VA power AC withstand voltage design
- Maximum voltage 5kV for Insulation resistance test
- Leakage current supports a variety of human body impedance simulation resistance (MD)
- 500VA high-power AC power output (only TH9130, TH9131 this function is optional)
- Open/short circuit detection OSC
- ARC detection function
- Crash voltage test function
- Single screen display test mode, time, voltage, current, resistance value, test steps
- List display function: Simultaneously display the test results of multi-step settings and sequential execution
- Storage: 100 files, 50 steps/file



RS232	USB HOST	USB DEVICE	HANDLER	LAN
standard	standard	standard	standard	standard

Dimension(mm):430mm(W)x132mm(H)x550mm(D)
Weight: 40kg

Application

- Comprehensive electrical performance test and analysis of household appliances
- Comprehensive test and analysis of lighting appliances
- Motor comprehensive analysis test
- Test and analysis of high-power electrical appliances
- Comprehensive test and analysis of electronic components
- Medical electrical comprehensive test analysis

Specifications

Model				TH9130	TH9131	TH9130A	TH9131A	
Withstand Voltage Test								
Outout Voltage	AC	Range		0.05 - 5.0kV				
		Waveform		50/60Hz±0.1% Sine Wave				
		Oputput Power		500VA (5.0kV/100mA)	200VA	500VA	200VA	
	DC	Range		0.05 - 6.0kV				
		Oputput Power		150VA (6.0kV/25mA)	120VA	150VA	120VA	
	Load Change Rate		±(1% set value+10V) (Rated power)					
	Voltage Resolution		2V					
Voltage Accuracy		±(1% set value+5V)						
Output Current	AC	Range	V≤4kV	0.001mA - 120mA	0.001mA - 40mA	0.001mA - 120mA	0.001mA - 40mA	
			V>4kV	0.001mA - 100mA	0.001mA - 40mA	0.001mA - 100mA	0.001mA - 40mA	
		Resolution		0.001mA				
		Accuracy	120mA	0.1mA-120.0mA ± (1% Reading +0.6mA)				
			30mA	0.01mA-29.99mA ± (1% Reading +0.15mA)				
			3mA	0.001mA-2.999mA ± (1% Reading +0.015mA)				
	DC	Range	V≥1.5kV	0.0001mA - 25mA	0.0001mA - 12mA	0.0001mA - 25mA	0.0001mA - 20mA	
			V<1.5kV	0.0001mA - 20mA	0.0001mA - 12mA	0.0001mA - 20mA	0.0001mA - 10mA	
		Resolution		0.1μA				
		Accuracy	25mA	0.01mA-25.00mA ± (1% Reading +0.12mA)				
			3mA	0.001mA-2.999mA ± (1% Reading +0.015mA)				
			5.1μA	0.1μA-299.9μA ± (1% Reading +1.5μA)				
Time Setting	Testing time			0.3 - 999s, 0 means continuous testing				
	Rise Time/ Fall time			0.1 - 999s, 0 means off				
	Waiting time			0.1 - 999s, 0 means off (only DC withstand voltage)				
ARC Detection	AC			1.0mA - 20.0mA	1.0mA - 20.0mA	1.0mA - 20.0mA	1.0mA - 20.0mA	
	DC			1.0mA - 10.0mA				

Safety Tester/Hipot Tester

IV. TH9130 Series Multifunction Safety Compliance Analyzer

Maximum short circuit current (AC test)				200mA	80mA	200mA	80mA
Quick discharge function				Automatic discharge after test (DCW)			
Insulation Resistance Test							
Voltage	Output			DC:0.05 - 5.0kV			
	Resolution			2V			
	Accuracy			±(1% Reading +5V)			
Resistance	Test Range			0.1MΩ - 50.0GΩ			
	Accuracy	V≥500V	1MΩ - 1GΩ	±(3% Reading +1M)			
			1GΩ - 10GΩ	±(7% Reading +0.2G)			
			10GΩ - 50GΩ	±(10% Reading +0.5G)			
		V<500V	1MΩ - 1GΩ	±(5% Reading +100V/Vs*10M)			
Time Setting	Testing time			0.3 - 999s, 0 means continuous testing			
	Rise Time/ Fall time			0.1 - 999s, 0 means off			
	Waiting time			0.1 - 999s, 0 means off			
Quick discharge function				Automatic discharge after test			
AC Ground Bond Test							
Output Current	Range			1.00 - 40.00A			
	Resolution			0.01A			
	Accuracy			±(2% set value +2 Digit)			
Output Voltage	Range			3.00 - 8.00V			
	Resolution			0.01V			
	Accuracy			±(2% set value +3 Digit)			
Test Frequency				50/60Hz±0.1%			
Output Regulation				±(1% Output Value+0.02A)			
Resistance Test	Range and Accuracy	1.00 - 3.00A		0 - 600mΩ± (3% Reading +3 Digit)			
		3.01 - 10.00A		0 - 600mΩ± (2% Reading +2 Digit)			
		10.01 - 30.00A		0 - 200mΩ± (2% Reading +2 Digit)			
		30.01 - 40.00A		0 - 150mΩ± (2% Reading +2 Digit)			
Test Time				0.5 - 999s, 0 means continuous testing			
Continuity test							
Test Current	0.0001A - 0.1A			0.00 - 10000Ω			
Resistance Accuracy	0 - 1000Ω			± (1% Reading +3 Digi)			
	1001 - 10000Ω			± (1% Reading +10 Digi)			
Test Time				0.3 - 999s, 0 means continuous testing			
Electrical performance test							
Voltage Test	Range			0.0 - 277.0V			-----
	Resolution			0.1V			-----
	Accuracy			± (1.5% Reading +2 Digit) (30 - 277V)			-----
Current Test	Range			0.00 - 16.00A			-----
	Resolution			0.01A			-----
	Accuracy			± (2% Reading +2 Digit)			-----
Power Test	Range			0 - 4500W			-----
	Resolution			1W			-----
	Accuracy			± (5% Reading +3W)			-----
Power Factor	Range			0.000 - 1.000			-----
	Resolution			0.001			-----
	Accuracy			± (8% Reading +2 Digit)			-----
Leakage Current	Range			0.00 - 10.00mA			-----
	Resolution			0.01mA			-----
	Accuracy			± (2% Reading +2 Digit)			-----
Test Time				0.1 - 999s, 0 means continuous testing			-----
Waiting Time				0.2 - 999s			-----

Safety Tester/Hipot Tester

IV. TH9130 Series Multifunction Safety Compliance Analyzer

Leakage Current Test									
Input Voltage	Range		0 - 277Vac,16Aac Max		-----				
	Accuracy		±（1.5% Reading +2 Digit）（30 - 277V）		-----				
Leakage Current	Test Range		0.0μA - 10.00mA		-----				
	Test Frequency		DC, 15Hz - 1MHz		-----				
Test Time	AC+DC		0.5 - 999s, 0 means continuous testing		-----				
	AC/DC		0.1 - 999s, 0 means continuous testing		-----				
Waiting Time			AC+DC		0.5 - 999s				
			AC/DC		1.8 - 999s Auto Range 1.3 - 999s Fixed Range				
Body Impedance Network (MD)	A:		UL544NP、UL484、IEC60598、UL1363、UL923、UL471、UL867、UL697		-----				
	B:		UL544P		-----				
	C:		UL2601 - 1、IEC60601 - 1、EN60601 - 1		-----				
	D:		UL1563		-----				
	E:		IEC60990Fig4U2、IEC60950 - 1、IEC60335 - 1、IEC60598 - 1、UL484、IEC60065、IEC61010		-----				
	F:		IEC60990Fig5U3、IEC60598 - 1		-----				
	G:		Frequency Detection 1kΩ		-----				
MDA-G Devices precision	Resistance Precision		±1%		-----				
	Capacitance Precision		±5%		-----				
MD Voltage Protection			30V Peak Value or 30Vdc		-----				
30V Peak Value or 30Vdc			G - L、PH - L、PH - PL		-----				
Leakage Current Range eEffective Value RMS	MD main resistance		Range		-----				
	0.5kΩ / 1kΩ / 1.5kΩ		0.0μA - 10.00mA		-----				
	Resolution	Auto Range & Fixed Range 1 - 2 & Fixed Range 3 (1k&1.5kMD)		<1000μA	0.1μA	-----			
				1000μA - 8400μA	1μA	-----			
				>8400μA	0.01mA	-----			
				<8400μA	1μA	-----			
				>8400μA	0.01mA	-----			
				Fixed range 3 (0.5kMD) & Fixed range 4 - 6					
	Range Accuracy	Range	Test Mode	Frequency		Accuracy			
		Range 1 - 5	AC+DC	DC		±（2%Reading+3 Digit）			
				15Hz<f<100kHz		±（2%Reading+3 Digit）			
				100kHz≤f≤1MHz		±（5%Reading）>10.0μA			
				15Hz<f≤30Hz		±（3%Reading+5 Digit）			
				30Hz<f<100kHz		±（2%Reading+3 Digit）			
				100kHz≤f≤1MHz		±（5%Reading）>10.0μA			
			DC only	DC		±（2%Reading+3 Digit）>10.0μA			
				Range 6	AC+DC	DC		±（5%Reading）>10.0μA	
						15Hz<f<100kHz			
AC only		15Hz<f≤30Hz							
		30Hz<f<100kHz							
DC only		DC							
Leakage Current Range Peak Value PEAK	MD main resistance		Range		-----				
	0.5kΩ / 1kΩ / 1.5kΩ		0.0μA - 10.00mA		-----				
	Resolution	Auto Range & Fixed Range 1 - 2 & Fixed Range 3 (1k&1.5kMD)		<1000μA	0.1μA	-----			
				1000μA - 8400μA	1μA	-----			
				>8400μA	0.01mA	-----			
				<8400μA	1μA	-----			
				>8400μA	0.01mA	-----			
				Fixed range 3 (0.5kMD) & Fixed range 4 - 6					
	Range Accuracy	Range	Test Mode	Frequency		Accuracy			
		Range1-5	AC+DC	DC		±（2%Reading+2μA）			
				15Hz≤f≤1MHz		±（10%Reading+2μA）			
				15Hz<f<1MHz		±（10%Reading+2μA）			
				DC		±（2%Reading+3 Digit）			
				15Hz<f<100kHz		±（10%Reading+2 Digit）			
				15Hz<f<100kHz		±（10%Reading+2 Digit）			
			Range6	AC+DC	DC		±（10%Reading+2 Digit）		
					15Hz<f<100kHz				
				AC only	15Hz<f<100kHz				
					15Hz<f<100kHz				

Safety Tester/Hipot Tester

IV. TH9130 Series Multifunction Safety Compliance Analyzer

Leakage Voltage Range Effective Value RMS	MD main resistance		Range		-----	
	0.5kΩ / 1kΩ / 1.5kΩ		0.0mV - 15.00V		-----	
	Resolution	Auto Range & Fixed Range 1 - 2 & Fixed Range 3 (1k&1.5kMD)		<1000mV	0.1mV	-----
				1000mV - 8400mV	1mV	-----
				>8400mV	0.01V	-----
		Fixed range 3 (0.5kMD) & Fixed range 4 - 6		<8400mV	1mV	-----
	>8400mV			0.01V	-----	
	Range Accuracy	Range	Test Mode	Frequency	Accuracy	-----
		Range1-5	AC+DC	DC	±（2%Reading+3Digit）	-----
				15Hz<f<100kHz	±（2%Reading+3Digit）	-----
				100kHz≤f≤1MHz	±（5%Reading）>10.0mV	-----
			AC only	15Hz<f≤30Hz	±（3%Reading+5Digit）	-----
				30Hz<f<100kHz	±（2%Reading+3Digit）	-----
				100kHz≤f≤1MHz	±（5%Reading）>10.0mV	-----
		Range6	AC+DC	DC	±（5%Reading）>10.0mV	-----
				15Hz<f<100kHz		-----
AC only			15Hz<f≤30Hz	-----		
			30Hz<f<100kHz	-----		
			DC only	DC		-----

Leakage Voltage Range Peak Value PEAK	MD main resistance		Range			-----
	0.5kΩ / 1kΩ / 1.5kΩ		0.0mV - 15.00V			-----
	Resolution	Auto Range & Fixed Range 1 - 2 & Fixed Range 3 (1k&1.5kMD)		<1000mV	0.1mV	-----
				1000mV - 8400mV	1mV	-----
				>8400mV	0.01V	-----
		Fixed range 3 (0.5kMD) & Fixed range 4 - 6		<8400mV	1mV	-----
	>8400mV			0.01V	-----	
	Range Accuracy	Range	Test Mode	Frequency	Accuracy	-----
		Range1-5	AC+DC	DC	±（2% Reading+2mV）	-----
				15Hz≤f≤1MHz	±（10% Reading+2mV）	-----
			AC only	15Hz<f<1MHz	±（10% Reading+2mV）	-----
				Range6	AC+DC	DC
15Hz<f<100kHz		±（10% Reading+2 Digit）	-----			
AC only		15Hz<f<100kHz	±（10% Reading+2 Digit）		-----	
			±（10% Reading+2 Digit）		-----	
OSC Open and Short Circuit Detection						
Sampling Standard Capacitance Range			0.001 - 40nF			
Open circuit judgment range			10% - 100%			
Short circuit judgment range			100% - 500%			
Safety Protection Function						
Electric Shock Protection			0.5mA±0.25mA Option: on or off			
Start Protection Interlock			The pin is grounded to allow high voltage output.			
Panel operation protection			key lock			
Alarm indication			Pass: short tone, green light; Fail: long tone, red light			
Electrical and leakage power short circuit protection			23A _{RMS} or Electric shock 68A _{PEAK}			
Hipot and ground synchronous output test			5kVac/30mAac and 30Aac/150mΩ(TH9131/TH9131A)			
Storage and Interface						
Internal memory			Can save 100 files, 50 steps per file.			
Standard interface			RS232、USB DEVICE、USB HOST、LAN、HANDLER			
Optional interface			GPIB			
Ambient temperature and humidity						
Parameter Comparasion Temperature			18℃ - 28℃， humidity:30% - 70%RH			
Normal Working Temperature			0℃ - 45℃， humidity:20% - 90%RH			
Storage Ambient Temperature			-10℃ - 55℃， humidity:<80%RH			
General Information						
Power Supply			100V - 240VAC， 47Hz - 63Hz			
Power			No load: <100W, Rated power:1200W			
Size（W）×（H）×（D）			430mm×132mm×550mm			
Weight			40kg	38kg	34kg 32kg	