

TM600-1500

THREE-PHASE ASYNCHRONOUS SQUIRREL CAGE MOTOR

Voltage:	220/380V(230/400V)
Current:	1.3A/2.3A
Frequency:	50Hz
Output power:	600W
Rotate speed:	1400rpm
Shaft height:	80mm
Dimension:	320x180x190mm
Weight:	9kg



TM600-1500DS

DOUBLE SPEED THREE-PHASE ASYNCHRONOUS SQUIRREL CAGE MOTOR

Voltage:	380V(400V)
Current:	1.5A/1.6A
Frequency:	50Hz
Output power:	600W
Rotate speed:	2800/1400rpm
Shaft height:	80mm
Dimension:	320x180x190mm
Weight:	9kg



SM600-1500SR

SINGLE-PHASE START & RUN CAPACITORS MOTOR

Voltage:	220V(230V)
Current:	4.2A
Frequency:	50Hz
Output power:	600W
Rotate speed:	1400rpm
Shaft height:	80mm
Dimension:	310x180(195)x210mm
Weight:	12.5kg



SM600-1500S

SINGLE-PHASE START CAPACITOR MOTOR

Voltage:	220V(230V)
Current:	4.2A
Frequency:	50Hz
Output power:	300W
Rotate speed:	1400rpm
Shaft height:	80mm
Dimension:	310x180(195)x210mm
Weight:	12.5kg



DM600-3000PM

PERMANENT MAGNET DC MOTOR

Armature voltage:	0~220VDC
Max. armature current:	3.3A
Max. output power:	600W
Max. rotate speed:	3000rpm
Shaft height:	80mm
Dimension:	260x180(190)x150mm
Weight:	9kg



DM600-3000SP

SEPARATED/SHUNT DC MOTOR

Armature & excitation voltage:	0~220VDC
Max. armature current:	3.3A
Max. excitation current:	0.14A
Max. output power:	600W
Max. rotate speed:	3000rpm
Shaft height:	80mm
Dimension:	280x180(200)x150mm
Weight:	13.5kg



DM600-3000SR

SERIES DC MOTOR

Armature & excitation voltage:	0~220VDC
Max. armature & excitation current:	4.3A
Max. output power:	600W
Max. rotate speed:	1800rpm
Shaft height:	80mm
Dimension:	280x180(200)x150mm
Weight:	13kg



DM600-3000CP

COMPOUND DC MOTOR

Armature voltage:	0~220VDC
Excitation voltage:	220VDC
Max. armature current:	3.3A
Excitation current:	0.13A
Max. output power:	500W
Max. rotate speed:	3000rpm
Shaft height:	80mm
Dimension:	280x180(200)x150mm
Weight:	13.5kg



UM600-3000SP

DC/AC UNIVERSAL MOTOR

Armature & excitation voltage:	220VDC/AC
Max. armature & excitation current:	DC 3.7A, AC 6.5A
Max. output power:	550W
Max. rotate speed:	3000rpm
Shaft height:	80mm
Dimension:	280x180(200)x150mm
Weight:	12.5kg



DG600-3000SP

DC GENERATOR

Excitation voltage:	0~220VDC
Excitation current:	0.14A
Max. output voltage:	220VDC
Max. output power:	600W
Max. rotate speed:	3000rpm
Shaft height:	80mm
Dimension:	280x180(200)x150mm
Weight:	13.5kg



TM600-1500SR

THREE-PHASE SLIP-RING ASYNCHRONOUS MOTOR

Voltage:	230V/400V
Current:	2.3A
Frequency:	50Hz
Output power:	600W
Rotate speed:	1250rpm
Shaft height:	80mm
Dimension:	325x180x180mm
Weight:	8.5kg



TM600-1500S

THREE-PHASE SYNCHRONOUS MOTOR/GENERATOR

Voltage:	230V/400V
Current:	4.7A
Frequency:	50Hz
Rotor voltage:	24VDC
Rotor current:	2.6ADC
Output power:	400W
Rotate speed:	1500rpm
Shaft height:	80mm
Dimension:	325x180x180mm
Weight:	9.5kg

