

Wkrętaki elektryczne SD



Specyfikacja

Model	Zakres Momentu		Prędkość Obrotów (bez obciążenia) [rpm]		Napięcie Wejściowe	Waga	Średnica Wkrętu	Średnica Bita	Numer katalogowy	
	Kgf cm	N m	Max	Min					zwykłe	ESD
SD-A300L	0.2-3.5	0.02-0.34	1000	650	30V	330	M1.2-M2.5	Ø 4mm	202958	202980
SD-A400L	0.3-6.5	0.03-0.63	1000	650		330	M1.4-M2.6	Ø4mm	202956	202981
SD-A450L	1-10	0.1-1	1000	650		430	M1.4-M3.0	Ø5mm	202959	202982
SD-A450LF	1-10	0.1-1	2000	1200		430	M1.4-M3,0	Ø5mm	202970	202983
SD-A500L	2-12	0.2-1.18	1000	650		430	M1.6-M3.0	Ø5mm	202954	202984
SD-A500LF	2-12	0.2-1.18	2000	1300		430	M1.6-M3.0	Ø5mm	202971	202985
SD-A550L	3-19	0.29-1.86	1000	650		430	M2.3-M3.5	Ø5mm	202972	202986
SD-A600L	5-25	0.5-2.45	1000	650		740	M2.6-M4.0	¼ hex	202973	202987
SD-A600LF	5-23	0.5-2.25	2000	1300		740	M2.6-M4.0	¼ hex	202974	202988
SD-A620L	10-30	0.98-2.94	1000	650		740	M2.6-M4.5	¼ hex	202975	202989
SD-A630L	10-35	0.98-3.43	500	350		740	M3.0-M5.0	¼ hex	202977	202991
SD-A700L	15-45	1.47-4.41	500	350		740	M3.5-M5.5	¼ hex	202978	202992

