



Model	8015D5	8015LED-A	8015LED-U	8017DLED	8095LED-2-A
Nr katalogowy	312768	312769	312737	312778	312745
Podświetlenie	3-12W LED SMD	5-20W LED SMD	2-20W LED SMD	3-23W LED SMD	7W LED SMD
Temp. barwowa	6000-7000K	6000-7000K	6000-7000K	3000/6500K	6000-7000K
Lumeny	1350 lm	1600 lm	1600 lm	2400 lm	480 lm
Soczewka	-	-	-	-	78x127mm
Powiększenie	-	-	-	-	3 dpt/1,75x
Długość ramienia	900mm	900mm	900mm	900mm	700mm
Zasilanie	AC 230V	AC 230V	DC 24V	DC 24V	DC 21V



Model	8066D2LED-A-7C	8066LED-A	8066LED-2-A	8066D2LED-A-7C	8066LED-A
Nr katalogowy	312701	312728	312751	312702	312700
Podświetlenie	9W LED SMD	9W LED SMD	2-10W LED SMD	9W LED SMD	9W LED SMD
Temp. barwowa	6000-7000K	6000-7000K	6000-7000K	6000-7000K	6000-7000K
Lumeny	680 lm	610 lm	760 lm	680 lm	610 lm
Soczewka	Ø127mm	Ø127mm	Ø127mm	Ø127mm	Ø127mm
Powiększenie	3 dpt/1,75x	3 dpt/1,75x	3 dpt/1,75x	5 dpt/2,25x	5 dpt/2,25x
Długość ramienia	900mm	900mm	900mm	900mm	900mm
Zasilanie	AC 230V	AC 230V	AC 230V	AC 230V	AC 230V



Model	8060LED-U-A	8066D3LED-U	8066LED-2-A	8060LED-2	8066D2LED-A
Nr katalogowy	312718	312754	312752	312753	312726
Podświetlenie	9W LED SMD	2-10W LED SMD	2-10W LED SMD	2-10W LED SMD	9W LED SMD
Temp. barwowa	6000-7000K	6000-7000K	6000-7000K	2700/6500K	6000-7000K
Lumeny	630 lm	760 lm	760 lm	700 lm	680 lm
Soczewka	Ø127mm	Ø127mm	Ø127mm	Ø127mm	Ø127mm
Powiększenie	5 dpt/2,25x	5 dpt/2,25x	5 dpt/2,25x	5 dpt/2,25x	8 dpt/3,0x
Długość ramienia	900mm	900mm	900mm	900mm	900mm
Zasilanie	AC 230V	DC 24V	AC 230V	DC 24V	AC 230V





Model	8070LED-U	8062D3LED	8067LED-U	8069LED-A	8069D2LED-A
Nr katalogowy	312756	312719	312744	312741	312755
Podświetlenie	2-12W LED SMD	12W LED	2-20W LED SMD	9W LED SMD	2-10W LED SMD
Temp. barwowa	6000-7000K	6000-7000K	6000-7000K	6000-7000K	6000-7000K
Lumeny	1000 lm	910 lm	1400 lm	600 lm	790 lm
Soczewka	Ø152mm	Ø177mm	177x132mm	190x157mm	190x157mm
Powiększenie	5 dpt/2,25x	5 dpt/2,25x	3 dpt/1,75x	5 dpt/2,25x	5 dpt/2,25x
Długość ramienia	900mm	900mm	900mm	900mm	900mm
Zasilanie	DC 24V	AC 230V	DC 24V	AC 230V	AC 230V



Model	8066D2 ESD	8069D2LED-A ESD	8015LED-A ESD
Nr katalogowy	312739	312760	312759
Podświetlenie	9W LED SMD	2-10W LED SMD	5-20W LED SMD
Temp. barwowa	6000-7000K	6000-7000K	6000-7000K
Lumeny	600 lm	730 lm	1100 lm
Soczewka	Ø127mm	190x157mm	-
Powiększenie	5 dpt/2,25x	5 dpt/2,25x	-
Długość ramienia	900mm	900mm	900mm
Zasilanie	AC 230V	AC 230V	AC 230V



	Mocowania:			Podstawy:	
Nr kat.	312747	312724	312709	312710	312740

